

RECUPERATOR AIR EXPERT 600 V EPP

Device features

- Floor standing or wall-mounted unit (mounting bracket included)
- Counter flow heat exchanger with up to 98% efficiency (Basic or Classic) or enthalpy heat exchanger with up to 85% efficiency (Premium version)
- Energy-efficient fans EBM-PAPST
- Automatic by-pass 100% (Classic and Premium versions)
- Room module NANO ONE (Basic version) or NANO COLOR (Classic and Premium version) as standard
- Modulated pre-heater to prevent exchanger freezing (Classic and Premium versions)
- EPP (expanded polypropylene) design with excellent acoustic and thermal properties
- Control via smartphone (Android, iOS) - necessarily with iNEXT module
- Fitted with G4 (extract) and M5 and F7 (supply) filters
- Use of a CSF module is possible - balanced air flow function
- Can be combined with sensors: SHC (measuring CO2 concentration in rooms), SHK (measuring humidity and temperature in the ventilation duct), SHW (measuring humidity in rooms) and ACS-1 (measuring CO2 and PM2.5 and PM10)
- Cleanable heat exchanger





BASIC / CLASSIC



PREMIUM



Technical drawing



BASIC / CLASSIC



RECUPERATOR AIR EXPERT 600 V EPP

Technical data

TECHNICAL INFORMATION	AIR EXPERT 600 V BASIC	AIR EXPERT 600 V CLASSIC	AIR EXPERT 600 V PREMIUM
Supply voltage	230 V / 50 Hz		
Fan	2 x radial with EC motor EBM-PAPST		
Maximum fan power	2 pcs. x 170 W		
Maximum current consumption by fan	2 x 1.8 A		
Fan speed	3950 rpm		
Maximum discharge air temperature	-20 to +50 °C		
Heat exchanger type	counterflow plate heat exchanger	counterflow plate heat exchanger	enthalpy counterflow plate heat exchanger
Maximum exchanger efficiency	up to 98%		
Heat exchanger material	Polystyrene		
Housing material	EPP / painted steel		
Insulation	EPP		
Filter – air inlet	M5 + F7		
Filter – extracted air	G4		
Air spigots diameters	Ø200 mm		
Weight	32 kg		
Output at 100Pa	600 m ³ /h		
Controller type	Aero 4	Aero 4	Aero 4
Room module	Nano one	Nano colour	Nano colour
Dimensions [length x width x height]	930 mm x 770 mm x 600 mm		
Preheat coil power	None	2 kW	2 kW
Noise level	65 dB	65 dB	65 dB
Energy rating	A	A	A
Preheater current consumption	None	8.7 A	8.7 A
Total device power		2.35kW	2.35kW
Total current consumption		15.39 A	15.39 A
Bypass	None	Automatic	Automatic
Internet module	Optional	Yes	Yes
CSF module	Optional	Optional	Optional

